Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: daytime®

Supplier's address: Waltron GmbH daytime® Support, Sapelloh 51, 31606 Warmsen, DE

Model identifier: onex20 fresh

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type	-		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein
Colour-tuneable light source:	Nein	Envelope:	-
High luminance light source:	Nein		
Anti-glare shield:	Nein	Dimmable:	Only with specific dimmers

Product parameters

Parameter		Value	Parameter	Value			
General product parameters:							
Energy consump mode (kWh/1000 up to the nearest	0 h), rounded	5	Energy efficiency class	C			
Useful luminous indicating if it ref in a sphere (360 cone (120º) or in (90º)	ers to the flux D ^o), in a wide	750 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	7 000			
On-mode po expressed in W	wer (P _{on}),	4,8	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
Networked stand for CLS, express rounded to the se	ed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	85			
Outer	Height	14	Spectral power	See image			
dimensions	Width	165	distribution in the	in last page			

without separate control gear, lighting control parts and non- lighting control parts,	Depth	20	range 250 nm to 800 nm, at full-load	
if any (millimetre)				
Claim of equivale	ent power ^(a)	-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,294 0,295
Parameters for d	irectional light s	ources:		
Peak luminous in	tensity (cd)	202	Beam angle in degrees, or the range of beam angles that can be set	120
Parameters for L	ED and OLED lig	ht sources:	1	
R9 colour render	ing index value	34	Survival factor	-
the lumen mainte	enance factor	1,00		
(a), , not applicable				

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

